


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm					
NAME: ALT55-15G30-F		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:46		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 56.77 lm/W
MODEL	3000K CRI90	I _{max} (cd)	1713	S/MH(C0/180)	0.65	
NOMINAL POWER(W)	15	LOR(%)	100.0	S/MH(C90/270)	0.65	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	857.29	η UP,DN(C0-180)	0.0,45.0	
NOMINAL FLUX(lm)	857.294	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,55.0	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.50	
TEST VOLTAGE(V)	225.1	η down(%)	100.0	CIBSE SHR MAX	0.65	



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: AE
 Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 7.240m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1230	1206	1240	1358	1474	1506	1452	1327	0- 10	144.3	144.3	16.8,16.8
20	658.0	619.5	617.0	717.5	857.4	904.2	836.2	730.3	10- 20	287.1	431.3	50.3,50.3
30	293.5	261.9	247.2	304.6	372.0	405.5	386.6	323.5	20- 30	232.0	663.4	77.4,77.4
40	93.34	80.94	78.82	104.2	126.1	137.5	132.8	105.1	30- 40	121.5	784.9	91.6,91.6
50	25.88	22.99	22.59	27.66	32.95	38.75	39.83	29.52	40- 50	47.01	831.9	97,97
60	9.025	8.034	7.632	9.159	10.55	12.11	12.89	10.64	50- 60	15.68	847.6	98.9,98.9
70	3.915	3.345	3.231	4.455	5.215	5.963	5.659	4.697	60- 70	6.818	854.4	99.7,99.7
80	0.5391	0.4228	0.4072	0.4566	0.5022	1.066	1.059	0.4930	70- 80	2.470	856.9	100,100
90	0.4953	0.5522	0.4929	0.4413	0.2044	0.2115	0.2034	0.2031	80- 90	0.4097	857.3	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 814.84 lm

%lum = 95.0%

%lamp = 95.0%

Conical surface Flux(120deg): 847.6 lm

%lum = 98.9%


%lamp = 98.9%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1170	1039
80	700	531
75	1651	946
70	2581	2141
65	3260	2716
60	4070	3458
55	5651	5001
50	9077	7961
45	15101	12916


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.07	1.09	1.07	1.05	1.05	1.03	1.02	1.01	.00	.99	.98	.97	.96	.94
2.0	1.04	1.00	.97	1.02	.99	.96	.99	.96	.94	.96	.94	.92	.93	.91	.90	.88
3.0	.97	.93	.89	.96	.92	.88	.94	.90	.87	.91	.88	.86	.89	.86	.84	.83
4.0	.92	.87	.83	.91	.86	.82	.88	.84	.81	.87	.83	.80	.85	.82	.79	.78
5.0	.87	.81	.77	.86	.81	.77	.84	.79	.76	.82	.78	.75	.81	.77	.75	.73
6.0	.82	.76	.72	.81	.76	.72	.80	.75	.72	.78	.74	.71	.77	.73	.71	.69
7.0	.78	.72	.68	.77	.72	.68	.76	.71	.68	.75	.70	.67	.73	.70	.67	.66
8.0	.74	.68	.64	.73	.68	.64	.72	.67	.64	.71	.67	.64	.70	.66	.64	.62
9.0	.70	.65	.61	.70	.65	.61	.69	.64	.61	.68	.64	.61	.67	.63	.60	.59
10.0	.67	.62	.58	.67	.62	.58	.66	.61	.58	.65	.61	.58	.64	.60	.58	.56



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm					
NAME: ALT55-15G30-F			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:46		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.171	.097	.031	.164	.093	.030	.151	.087	.028	.140	.081	.026	.129	.075	.024	
2.0	.162	.089	.027	.157	.086	.027	.146	.081	.025	.137	.077	.024	.128	.072	.023	
3.0	.154	.082	.025	.149	.080	.024	.140	.076	.023	.132	.072	.022	.124	.069	.021	
4.0	.146	.076	.022	.142	.074	.022	.134	.071	.021	.127	.068	.021	.120	.065	.020	
5.0	.139	.071	.020	.135	.069	.020	.128	.067	.020	.122	.064	.019	.116	.062	.019	
6.0	.132	.066	.019	.129	.065	.019	.123	.063	.018	.118	.061	.018	.112	.059	.018	
7.0	.126	.062	.018	.123	.061	.017	.118	.060	.017	.113	.058	.017	.109	.056	.017	
8.0	.120	.059	.016	.118	.058	.016	.113	.057	.016	.109	.055	.016	.105	.054	.016	
9.0	.115	.056	.016	.113	.055	.015	.109	.054	.015	.105	.053	.015	.101	.051	.015	
10.0	.110	.053	.015	.108	.052	.015	.104	.051	.014	.101	.050	.014	.098	.049	.014	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.155	.133	.114	.133	.114	.098	.091	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.142	.114	.091	.122	.098	.079	.084	.068	.055	.048	.040	.033	.016	.013	.011	
4.0	.131	.099	.074	.113	.085	.064	.078	.059	.045	.045	.035	.027	.014	.011	.009	
5.0	.122	.087	.061	.105	.075	.053	.072	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.115	.078	.051	.098	.067	.044	.068	.047	.031	.039	.028	.019	.013	.009	.006	
7.0	.108	.070	.043	.093	.061	.038	.064	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.102	.063	.037	.088	.055	.032	.061	.039	.023	.035	.023	.014	.011	.007	.005	
9.0	.097	.058	.032	.083	.050	.028	.058	.035	.020	.034	.021	.012	.011	.007	.004	
10.0	.092	.054	.028	.079	.047	.025	.055	.033	.017	.032	.019	.010	.010	.006	.003	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm											
NAME: ALT55-15G30-F					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:46			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		16.3	17.2	16.6	17.4	17.6	15.4	16.3	15.6	16.4	16.6
	3H	16.3	17.1	16.6	17.3	17.5	15.3	16.2	15.6	16.4	16.6
	4H	16.3	17.1	16.6	17.3	17.5	15.3	16.1	15.6	16.3	16.5
	6H	16.2	16.9	16.5	17.2	17.4	15.2	15.9	15.5	16.2	16.4
	8H	16.2	16.9	16.5	17.1	17.4	15.2	15.9	15.5	16.1	16.4
	12H	16.1	16.8	16.4	17.1	17.3	15.1	15.8	15.4	16.1	16.3
4H	2H	16.2	17.0	16.5	17.2	17.4	15.2	16.0	15.5	16.2	16.5
	3H	16.2	16.9	16.5	17.1	17.4	15.2	15.9	15.6	16.2	16.5
	4H	16.2	16.8	16.5	17.1	17.4	15.2	15.8	15.5	16.1	16.4
	6H	16.1	16.6	16.4	16.9	17.3	15.1	15.6	15.5	16.0	16.3
	8H	16.0	16.5	16.4	16.9	17.2	15.0	15.5	15.4	15.9	16.3
	12H	16.0	16.4	16.4	16.8	17.2	15.0	15.5	15.4	15.8	16.2
8H	4H	16.0	16.5	16.4	16.9	17.2	15.1	15.6	15.4	15.9	16.3
	6H	15.9	16.3	16.4	16.7	17.1	15.0	15.4	15.4	15.8	16.2
	8H	15.9	16.3	16.3	16.7	17.1	14.9	15.3	15.4	15.7	16.1
	12H	15.9	16.2	16.3	16.6	17.1	14.9	15.2	15.3	15.6	16.1
12H	4H	16.0	16.4	16.4	16.8	17.2	15.0	15.5	15.4	15.8	16.2
	6H	15.9	16.2	16.3	16.7	17.1	14.9	15.3	15.4	15.7	16.1
	8H	15.8	16.1	16.3	16.6	17.1	14.9	15.2	15.3	15.6	16.1
Variations with the observer position at spacings:											
S = 1.0H	+ 2.7 / - 5.0					+ 2.6 / - 5.0					
1.5H	+ 4.3 / - 4.4					+ 4.1 / - 4.1					
2.0H	+ 4.5 / - 3.3					+ 4.2 / - 3.4					

CIE Pub.117, 857.3 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.5)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	86	80	76	86	80	76	85	79	76	72
0.80	94	88	84	93	87	84	92	87	83	80
1.00	99	93	89	98	92	89	96	92	88	84
1.25	103	97	94	102	97	93	100	96	93	88
1.50	105	101	97	104	100	97	102	98	96	91
2.00	108	104	101	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	112	108	105	110	107	104	106	104	102	96
4.00	114	111	109	112	109	107	108	106	104	97
5.00	115	113	111	113	111	109	109	107	106	98
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

AAI Figure

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:225.1V I:0.0700A P:15.10W PF:0.9610 Freq:0Hz Lamp Flux:857.294x1 lm		
NAME: ALT55-15G30-F	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:46	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	3581
L_0~180 (75) av	2014
L_0~180 (85) av	909
L_90~270 (65) av	3594
L_90~270 (75) av	1927
L_90~270 (85) av	905
L_45 (65) av	3636
L_45 (75) av	1999
L_45 (85) av	917

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: AE
Test Date: 2020-06-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```