


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:60		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 62.95 lm/W
MODEL	ALT70-27G30-15	I <sub>max</sub> (cd)	15292	S/MH(C0/180)	0.27	
NOMINAL POWER(W)	28	LOR(%)	100.0	S/MH(C90/270)	0.28	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	1731.1	η UP,DN(C0-180)	0.0,51.0	
NOMINAL FLUX(lm)	1731.07	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.0	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE(V)	225.1	η down(%)	100.0	CIBSE SHR MAX	1.00	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-06-16

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:


$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	$\%lum, lamp$
10	567.4	581.0	532.6	515.7	509.5	479.6	521.3	525.0	0- 10	901.8	901.8	52.1,52.1
20	92.24	95.97	88.95	84.09	86.56	82.93	87.77	83.41	10- 20	575.2	1477	85.3,85.3
30	16.49	16.82	15.65	14.17	15.77	14.71	15.83	14.29	20- 30	190.9	1668	96.4,96.4
40	3.216	3.293	2.981	2.590	3.120	2.979	3.281	2.560	30- 40	45.50	1713	99,99
50	0.7396	0.8762	0.6031	0.5496	0.6812	0.7879	0.7286	0.5716	40- 50	12.02	1725	99.7,99.7
60	0.1282	0.1056	0.1092	0.1044	0.1393	0.1356	0.1450	0.1390	50- 60	2.688	1728	99.8,99.8
70	0.0733	0.0654	0.0712	0.0693	0.0987	0.0975	0.1013	0.0974	60- 70	0.9433	1729	99.9,99.9
80	0.0936	0.0944	0.0931	0.0963	0.0987	0.1022	0.0990	0.0964	70- 80	0.9475	1730	99.9,99.9
90	0.1304	0.1304	0.1299	0.1307	0.0544	0.0544	0.0532	0.0563	80- 90	1.048	1731	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-06-16

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	4542	4558
80	1905	1897
75	1069	1038
70	757	737
65	718	656
60	907	773
55	1553	1107
50	4068	3321
45	7787	6925


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.13	1.12	1.10	1.11	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.00	.00	.99	.97
2.0	1.09	1.06	1.04	1.07	1.05	1.03	1.04	1.02	1.01	1.01	.00	.98	.99	.98	.96	.95
3.0	1.05	1.02	.99	1.04	1.01	.98	1.01	.99	.97	.99	.97	.95	.97	.95	.94	.93
4.0	1.02	.98	.95	1.01	.97	.95	.99	.96	.94	.97	.95	.93	.95	.93	.92	.91
5.0	.99	.95	.92	.98	.94	.92	.96	.93	.91	.95	.92	.90	.93	.91	.90	.89
6.0	.96	.92	.90	.95	.92	.89	.94	.91	.89	.93	.90	.88	.92	.89	.88	.87
7.0	.94	.90	.87	.93	.90	.87	.92	.89	.87	.91	.88	.86	.90	.88	.86	.85
8.0	.91	.88	.85	.91	.87	.85	.90	.87	.85	.89	.86	.85	.88	.86	.84	.83
9.0	.89	.86	.83	.89	.86	.83	.88	.85	.83	.88	.85	.83	.87	.84	.83	.82
10.0	.87	.84	.82	.87	.84	.82	.87	.84	.82	.86	.83	.81	.85	.83	.81	.80



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-06-16

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm									
NAME:				TYPE:			WEIGHT:		
SPEC.:				DIM.:			SERIAL No.:		
MFR.:				SUR.:60			Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.125	.071	.023	.119	.068	.022	.107	.061	.020	.095	.055	.018	.085	.049	.016	
2.0	.115	.063	.019	.110	.060	.019	.099	.055	.017	.090	.051	.016	.082	.046	.015	
3.0	.106	.056	.017	.102	.054	.016	.093	.051	.015	.086	.047	.014	.078	.043	.013	
4.0	.099	.051	.015	.095	.050	.015	.088	.047	.014	.081	.044	.013	.075	.041	.012	
5.0	.092	.047	.014	.089	.046	.013	.083	.043	.013	.078	.041	.012	.072	.039	.012	
6.0	.087	.043	.012	.084	.042	.012	.079	.040	.012	.074	.039	.011	.070	.037	.011	
7.0	.082	.040	.011	.080	.040	.011	.075	.038	.011	.071	.036	.011	.067	.035	.010	
8.0	.078	.038	.011	.076	.037	.011	.072	.036	.010	.068	.035	.010	.065	.033	.010	
9.0	.074	.036	.010	.072	.035	.010	.069	.034	.010	.066	.033	.009	.063	.032	.009	
10.0	.070	.034	.009	.069	.033	.009	.066	.032	.009	.063	.031	.009	.061	.030	.009	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.168	.158	.149	.143	.135	.128	.098	.093	.089	.056	.054	.052	.018	.017	.017	
2.0	.149	.133	.119	.127	.114	.103	.087	.079	.072	.050	.046	.042	.016	.015	.014	
3.0	.133	.113	.097	.114	.098	.085	.078	.068	.059	.045	.040	.035	.015	.013	.011	
4.0	.120	.098	.081	.103	.084	.070	.071	.059	.049	.041	.034	.029	.013	.011	.010	
5.0	.109	.085	.068	.093	.074	.059	.064	.051	.042	.037	.030	.025	.012	.010	.008	
6.0	.099	.075	.057	.085	.065	.050	.059	.045	.035	.034	.027	.021	.011	.009	.007	
7.0	.091	.067	.049	.078	.058	.043	.054	.040	.030	.032	.024	.018	.010	.008	.006	
8.0	.084	.060	.042	.073	.052	.037	.050	.036	.026	.029	.021	.016	.009	.007	.005	
9.0	.078	.054	.037	.068	.047	.032	.047	.033	.023	.027	.019	.014	.009	.006	.005	
10.0	.073	.049	.033	.063	.042	.028	.044	.030	.020	.026	.018	.012	.008	.006	.004	

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm											
NAME:					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:60			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	2H	7.1	7.6	7.3	7.8	7.9	6.9	7.4	7.1	7.6	7.7
	3H	7.0	7.5	7.2	7.7	7.8	6.8	7.3	7.0	7.5	7.7
	4H	6.9	7.4	7.2	7.6	7.8	6.7	7.2	7.0	7.4	7.6
	6H	6.9	7.4	7.2	7.6	7.8	6.7	7.2	7.0	7.4	7.7
	8H	7.0	7.4	7.2	7.7	7.9	6.8	7.2	7.1	7.5	7.7
	12H	7.1	7.5	7.4	7.8	8.0	6.9	7.4	7.2	7.6	7.9
4H	2H	6.9	7.4	7.1	7.6	7.8	6.7	7.2	6.9	7.4	7.6
	3H	6.7	7.2	7.0	7.4	7.7	6.5	7.0	6.9	7.3	7.5
	4H	6.7	7.1	7.0	7.4	7.7	6.5	6.9	6.8	7.2	7.5
	6H	6.7	7.1	7.1	7.4	7.8	6.6	6.9	6.9	7.3	7.6
	8H	6.8	7.2	7.2	7.5	7.9	6.7	7.0	7.1	7.4	7.7
	12H	7.1	7.4	7.5	7.8	8.2	7.0	7.3	7.4	7.6	8.0
8H	4H	6.6	6.9	6.9	7.3	7.6	6.4	6.7	6.8	7.1	7.4
	6H	6.7	7.0	7.1	7.4	7.8	6.5	6.8	6.9	7.2	7.6
	8H	6.9	7.2	7.3	7.6	8.0	6.7	7.0	7.2	7.4	7.9
	12H	7.3	7.6	7.8	8.0	8.5	7.2	7.4	7.7	7.9	8.3
12H	4H	6.5	6.8	6.9	7.2	7.6	6.4	6.7	6.8	7.0	7.4
	6H	6.7	6.9	7.1	7.4	7.8	6.5	6.8	7.0	7.2	7.6
	8H	7.0	7.2	7.4	7.6	8.1	6.8	7.0	7.3	7.5	7.9
Variations with the observer position at spacings:											
S = 1.0H	+ 2.8 / - 4.4					+ 2.4 / - 4.3					
1.5H	+ 4.6 / - 3.9					+ 4.3 / - 4.4					
2.0H	+ 3.7 / - 2.0					+ 3.9 / - 1.5					

CIE Pub.117, 1731 lm Total Lamp Luminous Flux Correct ( $8\log(F/F_0) = 1.9$ )

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	91	85	82	90	85	82	90	85	82	78
0.80	98	93	89	97	92	89	96	92	89	86
1.00	102	97	93	101	96	93	99	96	93	89
1.25	105	101	97	104	100	97	102	99	96	92
1.50	108	103	100	106	103	100	104	101	99	95
2.00	110	106	103	108	105	102	106	103	101	96
2.50	111	108	105	110	107	104	107	104	102	97
3.00	113	110	107	111	108	106	108	105	104	98
4.00	114	112	110	112	110	109	109	107	106	99
5.00	116	114	112	114	112	110	110	108	107	100
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16


$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:

Flux out:795.4 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-06-16

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: AE  
 Test Date: 2020-06-16

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity: 65.0%  
 Test Distance: 7.240m [K=1.0000]  
 Remarks:

## LED Avg.L Report

Test:U:225.1V I:0.1280A P:27.50W PF:0.9500 Freq:50.00Hz Lamp Flux:1731.07x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:60	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	794
L_0~180(75)av	1225
L_0~180(85)av	3847
L_90~270(65)av	781
L_90~270(75)av	1204
L_90~270(85)av	3881
L_45(65)av	725
L_45(75)av	1215
L_45(85)av	3982

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-06-16

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: AE  
Test Date: 2020-06-16

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity: 65.0%  
Test Distance: 7.240m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```