


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm					
NAME: TL44-28W-840-B-24-L		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:99		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 106.74 lm/W
MODEL	3000K CRI80	I _{max} (cd)	13858	S/MH(C0/180)	0.38	
NOMINAL POWER(W)	26	LOR(%)	100.0	S/MH(C90/270)	0.39	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	2871.2	η UP,DN(C0-180)	0.0,49.6	
NOMINAL FLUX(lm)	2871.18	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.4	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE(V)	225.6	η down(%)	100.0	CIBSE SHR MAX	1.00	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:WuXing
 Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	909.3	917.4	877.4	878.9	904.0	909.5	944.5	915.0	0- 10	1117	1117	38.9,38.9
20	133.9	138.1	127.2	132.5	141.6	133.6	136.5	130.3	10- 20	1112	2229	77.6,77.6
30	31.80	33.82	32.30	33.13	34.72	33.25	31.85	30.74	20- 30	296.6	2526	88,88
40	14.15	15.55	15.54	15.66	16.09	14.96	13.82	13.37	30- 40	137.4	2663	92.8,92.8
50	7.321	7.636	7.588	7.691	7.912	7.606	7.389	7.203	40- 50	81.45	2745	95.6,95.6
60	5.226	5.284	5.304	5.288	5.608	5.403	5.250	5.133	50- 60	56.24	2801	97.6,97.6
70	3.423	3.357	3.249	3.313	3.513	3.524	3.611	3.551	60- 70	42.20	2843	99,99
80	0.8369	0.8521	0.8647	0.9111	0.9008	0.8780	0.8906	0.8521	70- 80	24.09	2867	99.9,99.9
90	0.3111	0.3116	0.3071	0.3064	0.1852	0.1884	0.1884	0.1897	80- 90	3.852	2871	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

Conical surface Flux(90deg): 2709.4 lm

%lum = 94.4%

%lamp = 94.4%

Conical surface Flux(120deg): 2801 lm

%lum = 97.6%


%lamp = 97.6%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:WuXing
 Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	4164	4155
80	6288	6467
75	11485	11586
70	13058	12336
65	12656	12235
60	13636	13776
55	13931	14301
50	14859	15331
45	18205	19504


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.10	1.08	1.10	1.08	1.07	1.06	1.05	1.03	1.02	1.01	1.00	.99	.98	.97	.96
2.0	1.06	1.03	1.00	1.05	1.02	.99	1.02	.99	.97	.99	.97	.95	.96	.95	.93	.92
3.0	1.01	.98	.94	1.00	.97	.94	.98	.95	.92	.95	.93	.91	.93	.91	.89	.88
4.0	.97	.93	.90	.96	.92	.89	.94	.91	.88	.92	.89	.87	.90	.88	.86	.85
5.0	.93	.89	.86	.93	.88	.85	.91	.87	.85	.89	.86	.84	.88	.85	.83	.82
6.0	.90	.86	.83	.89	.85	.82	.88	.84	.82	.87	.84	.81	.86	.83	.81	.80
7.0	.87	.83	.80	.87	.82	.80	.86	.82	.79	.84	.81	.79	.83	.81	.78	.77
8.0	.85	.80	.77	.84	.80	.77	.83	.79	.77	.82	.79	.77	.81	.78	.76	.75
9.0	.82	.78	.75	.82	.78	.75	.81	.77	.75	.80	.77	.75	.79	.76	.74	.73
10.0	.80	.76	.73	.80	.76	.73	.79	.75	.73	.78	.75	.73	.78	.75	.72	.72



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:WuXing
 Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm					
NAME: TL44-28W-840-B-24-L			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:99		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.149	.085	.027	.143	.081	.026	.130	.075	.024	.119	.068	.022	.108	.063	.020	
2.0	.138	.076	.023	.133	.073	.023	.123	.068	.021	.113	.063	.020	.104	.059	.019	
3.0	.128	.068	.020	.124	.066	.020	.115	.062	.019	.107	.059	.018	.100	.055	.017	
4.0	.120	.062	.018	.116	.061	.018	.108	.058	.017	.102	.055	.016	.095	.052	.016	
5.0	.112	.057	.017	.109	.056	.016	.102	.053	.016	.097	.051	.015	.091	.049	.015	
6.0	.105	.053	.015	.102	.052	.015	.097	.050	.014	.092	.048	.014	.087	.046	.014	
7.0	.099	.049	.014	.097	.048	.014	.092	.047	.013	.088	.045	.013	.084	.043	.013	
8.0	.094	.046	.013	.092	.045	.013	.088	.044	.013	.084	.042	.012	.080	.041	.012	
9.0	.089	.043	.012	.087	.043	.012	.084	.041	.012	.080	.040	.012	.077	.039	.011	
10.0	.085	.041	.011	.083	.040	.011	.080	.039	.011	.077	.038	.011	.074	.037	.011	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.169	.158	.147	.145	.135	.127	.099	.093	.088	.057	.054	.051	.018	.017	.016	
2.0	.152	.133	.117	.130	.114	.101	.089	.079	.070	.051	.046	.041	.016	.015	.013	
3.0	.137	.113	.094	.118	.098	.082	.081	.068	.057	.047	.040	.034	.015	.013	.011	
4.0	.125	.098	.078	.107	.085	.067	.074	.059	.047	.043	.035	.028	.014	.011	.009	
5.0	.114	.086	.065	.098	.074	.056	.068	.052	.040	.039	.030	.024	.013	.010	.008	
6.0	.106	.076	.055	.091	.066	.048	.063	.046	.034	.036	.027	.020	.012	.009	.007	
7.0	.098	.068	.047	.084	.059	.041	.058	.041	.029	.034	.024	.017	.011	.008	.006	
8.0	.091	.061	.040	.078	.053	.035	.054	.037	.025	.032	.022	.015	.010	.007	.005	
9.0	.085	.055	.035	.073	.048	.031	.051	.034	.022	.030	.020	.013	.010	.007	.004	
10.0	.080	.051	.031	.069	.044	.027	.048	.031	.019	.028	.018	.011	.009	.006	.004	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm											
NAME: TL44-28W-840-B-24-L					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:99			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		12.1	12.8	12.3	13.0	13.1	12.2	12.9	12.4	13.0	13.2
	3H	13.4	14.0	13.6	14.2	14.4	13.4	14.0	13.6	14.2	14.4
	4H	14.0	14.6	14.2	14.8	15.0	13.9	14.5	14.2	14.8	15.0
	6H	14.2	14.7	14.4	15.0	15.2	14.1	14.7	14.4	14.9	15.2
	8H	14.1	14.7	14.4	15.0	15.2	14.1	14.7	14.4	14.9	15.2
	12H	14.1	14.7	14.4	14.9	15.2	14.1	14.6	14.4	14.9	15.2
4H	2H	12.6	13.2	12.9	13.4	13.6	12.7	13.3	12.9	13.5	13.7
	3H	14.1	14.7	14.4	14.9	15.2	14.1	14.6	14.4	14.9	15.1
	4H	14.8	15.3	15.1	15.6	15.9	14.7	15.2	15.1	15.5	15.8
	6H	15.0	15.5	15.4	15.8	16.1	15.0	15.4	15.3	15.7	16.1
	8H	15.0	15.4	15.4	15.8	16.1	15.0	15.4	15.3	15.7	16.1
	12H	15.0	15.4	15.4	15.7	16.1	14.9	15.3	15.3	15.7	16.1
8H	4H	14.9	15.4	15.3	15.7	16.1	14.9	15.3	15.3	15.7	16.0
	6H	15.2	15.6	15.6	16.0	16.4	15.2	15.5	15.6	15.9	16.3
	8H	15.2	15.5	15.7	15.9	16.4	15.2	15.5	15.6	15.9	16.3
	12H	15.2	15.5	15.7	15.9	16.4	15.2	15.4	15.6	15.9	16.3
12H	4H	14.9	15.3	15.3	15.7	16.1	14.9	15.2	15.3	15.6	16.0
	6H	15.2	15.5	15.6	15.9	16.3	15.1	15.4	15.6	15.9	16.3
	8H	15.2	15.5	15.7	15.9	16.4	15.1	15.4	15.6	15.9	16.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.4 / - 0.5					
1.5H	+ 0.5 / - 0.4					+ 0.6 / - 0.5					
2.0H	+ 0.5 / - 0.5					+ 0.6 / - 0.5					

CIE Pub.117, 2871 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 3.7$)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	87	81	77	86	80	77	73
0.80	94	89	85	94	88	85	93	88	84	81
1.00	99	93	89	98	93	89	96	92	89	85
1.25	103	97	94	102	97	93	100	96	93	88
1.50	105	101	97	104	100	97	102	98	96	91
2.00	108	104	101	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	111	108	105	110	107	104	106	104	102	95
4.00	114	111	109	112	109	107	108	106	104	97
5.00	115	113	111	113	111	109	109	107	106	98
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

AAI Figure

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:WuXing
Test Date:2018-11-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: WuXing
Test Date: 2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:225.5V I:0.1240A P:26.90W PF:0.9590 Freq:50.00Hz Lamp Flux:2871.18x1 lm		
NAME: TL44-28W-840-B-24-L	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:99	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	12838
L_0~180 (75) av	12053
L_0~180 (85) av	3603
L_90~270 (65) av	12727
L_90~270 (75) av	12156
L_90~270 (85) av	3603
L_45 (65) av	12741
L_45 (75) av	12093
L_45 (85) av	3631

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:WuXing
 Test Date:2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: WuXing
Test Date: 2018-11-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```